

Full Color stratified laminated

Due to the limitations of the internet and differences between display devices colours should only be considered as an indication.




LS201
Full color white



LS202
Full color black

Alucompact stratified laminated



LS251
White Alucompact




LS252
Black Alucompact

Stratified laminated



LS203
Brown



LS301
White with grey silk-screen

Laminated



LM001
White



LM501
Needlecord

Esacore laminated



LS271
Aluminium/white



LS272
Aluminium/black



LS273
Aluminium/red

Laminate

Also known as the "ant", the laminate which is used for the realization of our articles is called HPL: acronym for High Pressure Laminate, these panels are made of layers of material in cellulose fibre impregnated in thermosetting resins, irreversibly cohesive through a process of high pressure which is applied on a sheet of kraft paper decorative. It is very resistant and is also used for coatings external facades, bathrooms, kitchen floors and benches from work and any other hard surface. The laminate HPL is also suitable for high resistance of the surface to shock and / or various stresses and their incorruptibility during the time and in any environmental situation (use of chemical disinfectants, steam, humid environments or frequent contact with water). Plywood thickness HPL certificates are used for food and request in 1st class reaction to fire. Because of their very low permeability, plywood thickness HPL acting as a barrier against possible emissions of formaldehyde, thus maintaining the level of emissions below the thresholds for woody-based materials.

Full color

Laminate HPL colored uniformly throughout the thickness using layers of colored paper Kraft also in the internal stratification of the product.

Alucompact

The Alucompact ® is a laminate stratified high pressure with aluminum foil included in the stratification that give strong structural stability.

laminated

Laminate layered with external application of a sheet of colored kraft paper.

Esacore

It is a sandwich panel made up of a soul honeycomb aluminum between two surfaces and aluminum. It has high-performance mechanical and thanks to the use of 'core' in honeycomb, a light weight. For these characteristics, we use plated, laminate or veneer, for extension of the tables.

Maintenance and cleaning of shares in stratified and laminate

The cleaning. Should be cleaned with a damp cloth and neutral detergent containing no abrasive or acids. At the end, must be dried with a soft cloth.

To avoid. Avoiding detergents with alkaline components and the use of abrasive flakes, could ruin the finish on the laminate.

Attention. Do not drag objects and not cut directly on the plans, could create scratches.